

levelsmart™

Wireless Autofill



LEVEL-UP YOUR POOL GAME
...WITH LEVELSMART™



www.h2flow.net

Level-up your pool game, with the LevelSmart™ wireless autofill system. LevelSmart™ is an innovative device designed to help homeowners, property managers, builders and maintenance companies with the challenges of maintaining water levels in pools, spas, ponds, water features, and tanks.



SIMPLE INSTALLATION & COMPLETE AUTOMATION!

LevelSmart™ eliminates the chore of filling your pool manually and the risk of over-filling it. With 24-hour-per-day wireless monitoring, LevelSmart™ automatically maintains the water level of your pool, spa, pond, water feature, or tank.

LevelSmart™ can easily be installed to any new or existing application. American-made quality, combined with an innovative and patented proprietary sensing method, ensures that LevelSmart is the most reliable and user-friendly autofill system on the market.

WHY CHOOSE LEVELSMART?

- Eliminates manual filling with a hose
- Eliminates unreliable float level controllers
- No pool deck damage or construction required
- Built-in protection against overfilling
- Simple installation
- 1,000ft max. of wireless communication
- Installs to new or existing applications
- Optional online monitoring and alerts available
- Precision water adjustment
- Discrete wireless sensor
- No autofill maintenance after installation



GET MORE WITH LEVELSMART ONLINE

Upgrade to LevelSmart™ Online to get even more features and benefits, including:

- Remote monitoring from the online dashboard and LevelSmart™ App
- Water level information
- Temperature information
- Water consumption (gallons used)
- Autofill information
- Push notifications and alerts



KEY BENEFITS



Eliminates manual work of filling the pool



Prevents tripping over hoses and increases overall pool safety



Retrofits to any pool without construction



Saves the pool pump from running dry and burning out




Reduces water and energy consumption



Keeps your pool full and ready to use at all times

HOW IT WORKS

Positioned at the desired water level within the pool, the LevelSmart™ sensor wirelessly communicates with the LevelSmart™ valve controller. When necessary, the valve will open, allowing water into the pool and making it possible to maintain the desired water level.





SPECIFICATIONS

Environmental	Factory-sealed batteries and electronics
Valve	24VAC valve
Maximum operating temperature	130°F / 54°C
Minimum operating temperature	40°F / 4°C
Monitoring Cycles	7-minutes per 30-minutes. Up to 336 minutes of fill time per day
Communication	1,000 feet max. of 433MHz interference free, radio communication
Dimensions	Valve Controller (HxW): 3" x 3" (7.6 x 7.6 cm); total width 4.07" (10.34 cm), screw holes 3.55" (9 cm) center-to-center
	Level Sensor (HxW): 2.85" x 2.9" (7.24 x 7.37 cm)
	Valve (HxWxL): 5" x 4.5" x 2.5" (13 x 11 x 6 cm)
	Valve Controller cables: 24VAC Power cable 55" (140 cm); 24VAC Control cable 55" (140 cm)

Progress through Innovation™

Our innovative solutions are developed with a focus on controlling, monitoring and measuring flow. Contact your authorized H2flow Controls solutions provider to find out how our products can help you and your customers.

Find an authorized partner at www.h2flow.net/locate-a-partner

AC DRIVES | ANTI ENTRAPMENT DEVICES | AUTOFILL SYSTEMS | FLOW METERS

 888.635.0296

 sales@h2flow.net

 www.h2flow.net

©2023 H2flow Controls, Inc. All rights reserved.

H2flow reserves the right to make changes to specifications and product features without notice. Please contact H2flow or visit www.h2flow.net for the most up-to-date versions of our product literature.

LS Rev.1.3

